



Section 1: Product & Company Identification

Product Name: Weld Check® Developer (aerosol)
Product Number (s): 03107
Product Use: Developer for non-destructive weld testing

Manufacturer / Supplier Contact Information:

In United States:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

1-215-674-4300 (General)

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

In Canada:

CRC Canada Co.

2-1246 Lorimar Drive

Mississauga, Ontario L5S 1R2

www.crc-canada.ca

1-905-670-2291

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

Section 2: Hazards Identification

Emergency Overview

DANGER: Extremely Flammable. Eye Irritant. Contents Under Pressure
Appearance & Odor: White powder with solvent odor

Potential Health Effects:

ACUTE EFFECTS:

EYE: May cause eye irritation. Vapors may irritate eyes.

SKIN: Prolonged contact may cause irritation or defatting of the skin.

INHALATION: May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Eye watering, headaches, nausea dizziness and loss of coordination are signs that solvent levels are too high.

INGESTION: If aspirated (liquid enters the lungs), it may be rapidly absorbed through the lungs and result in injury to other body systems. May cause gastro-intestinal distress.

CHRONIC EFFECTS: Prolonged overexposure to solvents may lead to permanent brain and nervous system damage.

TARGET ORGANS: central nervous system

Medical Conditions Aggravated by Exposure: Unknown

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Name: **Weld Check® Developer** (aerosol)

Product Number (s): **03107**

Section 3: Composition/Information on Ingredients

COMPONENT	CAS -NUMBER	% by Wt.
Methyl ethyl ketone	78-93-3	60 – 70
Liquefied petroleum gas	68476-86-8	20 – 30
Talc	14807-96-6	5 – 10

Section 4: First Aid Measures

Eye Contact: Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

Skin Contact: Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

Ingestion: Do not induce vomiting. Call a physician immediately.

Note to Physicians: If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat symptomatically.

Section 5: Fire-Fighting Measures

Flammable Properties: This product is extremely flammable in accordance with aerosol flammability definitions.

Flash Point: 23°F / -5°C (TCC)
Autoignition Temperature: 759°F / 404°C

Upper Explosive Limit: 11
Lower Explosive Limit: 1

Fire and Explosion Data:

Suitable Extinguishing Media: water fog, foam, dry chemical or carbon dioxide

Products of Combustion: oxides of carbon

Explosion Hazards: Aerosol containers, when exposed to heat from fire, may build pressure and explode. Vapors can accumulate and create a flammable atmosphere.

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8. Avoid contact with skin and eyes.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

Methods for Containment & Clean-up: Remove sources of ignition. Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Recover or absorb spilled

Product Name: Weld Check® Developer (aerosol)

Product Number (s): 03107

material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Avoid contact with skin and eyes. Avoid breathing vapors. Do not use near sources of ignition, including open flame or sparks or on energized equipment. Do not heat material. Potentially toxic or irritating fumes may be evolved from heated material. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120°F / 49°C to prevent cans from rupturing.

Aerosol Storage Level: III

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Methyl ethyl ketone	200	NE	200	300	NE		ppm
Liquefied petroleum gas	1000	NE	1000	NE	NE		ppm
Talc	20 mppcf	NE	2	NE	NE		mg/m ³
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Controls and Protection:

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as butyl rubber. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: liquid (in container)
powder (dispensed product)

Color: white
Odor: solvent

Product Name: Weld Check® Developer (aerosol)

Product Number (s): 03107

Odor Threshold: ND
Specific Gravity: 0.81
Initial Boiling Point: 175.3 °F (79.6 °C)
Freezing Point: -124 °F (-86.6 °C)
Vapor Pressure: ND
Vapor Density: 2.4 (air = 1)
Evaporation Rate: moderate
Solubility: slight
Coefficient of water/oil distribution: ND
pH: NA
Volatile Organic Compounds: wt %: 93 g/L: 676 lbs./gal: 5.62

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: heat, sources of ignition

Incompatible Materials: strong oxidizers, nitric and acetic or sulfuric acids, amines

Hazardous Decomposition Products: oxides of carbon (thermal decomposition)

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

Acute Toxicity:

<u>Component</u>	<u>Oral LD50 (rat)</u>	<u>Dermal LD50 (rabbit)</u>	<u>Inhalation LC50 (rat)</u>
Methyl ethyl ketone	2740 mg/kg	> 5000 mg/kg	11,700 ppm/4H
Liquefied petroleum gas	No data	No data	No data
Talc	No data	No data	No data

Chronic Toxicity:

<u>Component</u>	<u>OSHA Carcinogen</u>	<u>IARC Carcinogen</u>	<u>NTP Carcinogen</u>	<u>Irritant eye</u>	<u>Sensitizer</u>
Methyl ethyl ketone	No	No	No	No	No
Liquefied petroleum gas	No	No	No	No	No
Talc	No	No	No	No data	Unknown

Reproductive Toxicity: No information available

Teratogenicity: No information available

Mutagenicity: No information available

Synergistic Effects: No information available

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Product Name: Weld Check® Developer (aerosol)

Product Number (s): 03107

Ecotoxicity: No information available
Persistence / Degradability: No information available
Bioaccumulation / Accumulation: No information available
Mobility in Environment: No information available

Section 13: Disposal Considerations

Waste Classification: The liquid product is a hazardous waste for the characteristics of ignitability and toxicity with the following potential waste codes: D001, D035. The dried powder is not expected to be a hazardous waste.
Aerosol containers should be fully emptied and depressurized before disposal. Empty containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

Section 14: Transport Information

US DOT (ground): UN1950, Aerosols, flammable, 2.1, limited quantity

ICAO/IATA (air): UN1950, Aerosols, flammable, 2.1, limited quantity

IMO/IMDG (water): UN1950, Aerosols, 2.1, limited quantity

Special Provisions: None

Section 15: Regulatory Information

U.S. Federal Regulations:

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: methyl ethyl ketone (5000 lbs)

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	Yes
	Reactive Hazard	No
	Release of Pressure	Yes
	Acute Health Hazard	Yes
	Chronic Health Hazard	No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:
None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): methyl ethyl ketone

Product Name: Weld Check® Developer (aerosol)

Product Number (s): 03107

Canadian Regulations:

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulation and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: A, B5, D2B

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.


European Union Regulations:

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

Additional Regulatory Information: None

Section 16: Other Information

HMIS® (II)	
Health:	1
Flammability:	4
Reactivity:	0
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick
CRC #: SP500988
Revision Date: 11/20/2014

Changes since last revision: formula change

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstract Service
CFR: Code of Federal Regulations
DOT: Department of Transportation
DSL: Domestic Substance List
g/L: grams per Liter
HMIS: Hazardous Materials Identification System
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization

IMDG: International Maritime Dangerous Goods
IMO: International Maritime Organization
lbs./gal: pounds per gallon
LC: Lethal Concentration
LD: Lethal Dose
NA: Not Applicable
ND: Not Determined
NIOSH: National Institute of Occupational Safety & Health
NFPA: National Fire Protection Association
NTP: National Toxicology Program

Product Name: Weld Check® Developer (aerosol)

Product Number (s): 03107

OSHA: Occupational Safety and Health Administration

PMCC: Pensky-Martens Closed Cup

PPE: Personal Protection Equipment

ppm: Parts per Million

RoHS: Restriction of Hazardous Substances

STEL: Short Term Exposure Limit

TCC: Tag Closed Cup

TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Information System