



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

PRODUCT DATA

LUBRIPLATE POWER HAMMER & CHISEL GREASE

DESCRIPTION

This heavy-duty, extreme pressure type, aluminum complex grease with moly, copper and graphite, is made for use on most types of heavy-duty power hammers.

ADVANTAGES

⇒ Greatly extends shaft and bushing life.



Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
NLGI Grade		2
Worked Penetration Range	ASTM D-217	265 - 295
Thickener Type		Aluminum Complex
Dropping Point (°F)	ASTM D-2265	514°F
4-Ball EP Test - OK Load	ASTM D-2596	520 kg.
4-Ball EP Test - Weld Load	ASTM D-2596	540 kg.
% Moly Present		1
% Copper Present		2
% Graphite Present		2
Viscosity @ 100°F (SUS)	ASTM D-88	1000 SUS
Viscosity @ 210°F (SUS)	ASTM D-88	73 SUS
Flash Point (COC) °F	ASTM D-92	420°F

PACKAGING AVAILABLE

Part No.

35 lb. Pail

L0190-035

120 lb. Quarter Size, Drum

L0190-039

Carton, 40/14 oz. Cartridges

L0190-098