

Simplex™ Boom

BOM106 For Strong Current, 50' x 18", 12" Draft Dimensions

Marine-grade aluminum connectors and a galvanized steel chain make this 5,000 lb. breaking strength non-absorbent floating boom great for containing oil spills and debris in strong currents.

- Round, closed-cell polyethylene foam flotation cylinders corral liquids and debris up to 6" above water line
- Skirting barrier hangs 12" below the water line to keep pollutants from creeping under; galvanized steel chain runs the length of the boom to add weight and rigidity
- Heavy-duty, 22-ounce vinyl-coated polyester is UV resistant for regular outdoor use; welded, reinforced seams help ensure long life
- Marine-grade aluminum universal slide connectors and attached toggle pins permit linking of multiple units
- Quality construction provides 5,000-lb. actual breaking strength
- Polypropylene handle/anchor point eases handling and securing for easy deployment
- High-visibility yellow for instant recognition in emergencies
- Conforms to OPA-90 specifications
- Cleans easily using detergents, steam or power washing
- Light-weight and easy to move; ideal in marinas, inland waterways or along shorelines
- Add PIG Oil-Only Booms to absorb petroleum-based pollutants
- Need a custom boom? Call 1-800-HOT-HOGS (468-4647)



Specifications

| | |
|---------------------|--|
| Style | Non-Absorbent Boom |
| Color | Yellow |
| Dimensions | 50' L x 18" H |
| Current Type | Strong Current |
| Intended Use | On Water |
| Sold as | 1 each |
| Weight | 100 lbs. |
| Composition | Boom - PVC Chain - Galvanized Steel |

| | |
|-----------------------------|-----------------|
| Application | Spill Response |
| Draft Dimensions | 12" |
| Freeboard Dimensions | 6" |
| UNSPSC | 24101907 |
| Pigalog® Page Number | <u>Page 193</u> |

Metric Equivalent

| | |
|-------------------|------------------|
| Dimensions | 15m L x 45.7cm H |
| Weight | 45.4 kg |

Technical Information

Certifications, Approvals and Ratings

AASHTO M-228 Erosion Class A

Technical Documents

33 CFR 154.1040

40 CFR 112.7

40 CFR 122.26



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com