

PIG® Oil-Only Absorbent Boom

BOM304 8" x 10', Absorbs up to 12 gal. per boom, 4 booms

Confine and absorb oil and fuel spills on land or water.

- Field-proven performance works in all conditions to absorb oil spills on land or water
- Floats to confine and soak up spills on water; hugs ground for land-based spills
- Tough outer mesh is UV resistant for long-term outdoor use without degradation; lets fluids easily pass through to filler material
- Rope running along length of boom withstands up to 400-lb. loads, adding strength for deployment and retrieval
- Spunbond polypropylene skin is UV resistant up to 12 months; meets NFPA 99 standards for static decay
- Booms float at surface for easy retrieval, even when saturated
- Absorbs and retains oils and oil-based liquids - including lubricants and fuels - without taking in a drop of water
- Strong, zinc-plated carbon steel attachment clips and rings allow you to link booms together for greater length
- Bright white color makes booms easier to see in outdoor environments and clearly shows saturation level
- Can be incinerated after use to reduce waste or for fuels blending



Specifications

Fluid Absorbed	Oils, Fuels, Other Oil-Based Liquids Only
Color	White
Dimensions	ext. dia. 8" x 10' L
Recycled Content	98% Pre-Consumer Recycled Polypropylene Filler
Absorbency	Up to 48 gal. per bag
Absorbency per	Up to 12 gal. per boom
Clip/Ring	Zinc Plated Carbon Steel
Configuration	Boom

Filler	Polypropylene
Skin/Outer Mesh	Skin - Polypropylene, Outer Mesh - Polyester
Sold as	4 booms per bag
Weight	45.5 lbs.
NSN (National Stock Number)	7930-01-436-8326
# per Pallet	8
Application	Spill Response
UNSPSC	47131907
Pigalog® Page Number	Page 65

Metric Equivalent

Absorbency per	Up to 45.4 L per boom
Absorbency	Up to 181.7 L per bag
Dimensions	ext. dia. 20.3cm x 3m L
Weight	20.6 kg

Technical Information

Certifications, Approvals and Ratings

NFPA 99

Technical Documents

[UV-Resistance Comparison Testing of Spunbond and Meltblown](#)

[Instructions for Using PIG® Absorbent Booms](#)

[PIG® Oil-Only Absorbents](#)

[40 CFR 112.7](#)

[40 CFR 122.26](#)



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com