

PIG® Poly Modular Spill Deck

PAK524 Holds (1) 55 gal. Plastic or Steel Drum, 26" x 26" x 5.75", 11 gal. Sump Capacity

Connectable, shared-sump decks let you build up to your required sump capacity to help meet containment regs.

- Patented "flow-through" sump design lets liquid pass freely from one sump to another to help you comply with containment regulations
- Modular design features exclusive bulkhead fittings and predrilled ports to connect to other decks; ready to use as soon as they arrive
- Mix and match the sections you need to fit your space and help meet sump capacity requirements
- Special tools and hardware to connect sections is included with each system
- Low-profile 5.75"H design is easy to load or unload; pumps and funnels are easy to access
- Textured grating adds traction and lifts out for easy sump access
- Translucent white sidewalls allow easy visual inspection
- We test all of our Containment Pallet designs at max load for months to ensure they can handle full capacity at your facility



Specifications

Holds	(1) 55 gal. Plastic or Steel Drum
Color	Black/White
Dimensions	26" W x 26" L x 5.75" H
Recycled Content	39% Post-Industrial Recycled Polyethylene
Load Capacity UDL	1500 lbs.
Sump Capacity	11 gal.
Double-Stackable Unit	No
Drain	None
Fork Truck Access	No Fork Truck Access
Grates	(1) 24" L x 24" W Grate
Use With Flammables	No
Sold as	1 each

Weight	25 lbs.
New Pig Patent	Patent 5,562,047; And Other Foreign Patents
# per Pallet	20
Composition	Sump - LDPE w/ UV Inhibitor Grate - Polyethylene
Includes	1 - PIG® Plug Assembly (PAK578) 1 - PIG® Poly Bulkhead Fitting (PAK561) 1 - 24" L x 24" W x 2.63" H Grate 1 - T-Strip 1 - Wrench 1 - Instruction Booklet
UNSPSC	24101905
Pigalog® Page Number	<u>Page 375</u>

Metric Equivalent

Dimensions	66cm W x 66cm L x 14.6cm H
Load Capacity UDL	680.4 kg
Sump Capacity	41.6 L
Weight	11.3 kg

Technical Information

Technical Documents

LDPE Products

Instructions for PIG Poly Modular Spill Deck

40 CFR 112.7

40 CFR 122.26

40 CFR 264.175

Disclaimers

Flammables Notice

If using this product with flammable liquids, please consider the regulations that apply to storage and handling of flammable liquids and the safety of this application, specifically flammable vapors, static discharge and heat sources. For further assistance, please call Technical Services.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com

