

PIG® Economy 4-Drum Poly Spill Containment Pallet

PAK606 Holds (4) 55 gal. Steel Drums, 53" x 53" x 12", 66 gal. Sump Capacity



This cost-effective drum pallet shares many features with our more expensive models - plus it's made from recycled content!

- These pallets may be economical, but they're strong enough to handle long-term storage of fully loaded steel drums
- Low-density polyethylene (LDPE) construction resists UV rays, rust, corrosion and most chemicals
- Textured grating adds traction and lifts out for easy sump access
- 4-way forklift entry allows access from any direction for easy movement (unloaded only)
- We test all of our Containment Pallet designs at max load for months to ensure they can handle full capacity at your facility



Item#	Description	Dimensions	Weight
PAK606-WOD	Without Drain	53" W x 53" L x 12" H	85 lbs.
PAK606-WD	With Drain	53" W x 53" L x 12" H	85 lbs.

Metric Equivalent:

Item#	Description	Dimensions	Weight
PAK606-WOD	Without Drain	134.6cm W x 134.6cm L x 30.5cm H	38.6 kg
PAK606-WD	With Drain	134.6cm W x 134.6cm L x 30.5cm H	38.6 kg

Specifications

Holds	(4) 55 gal. Steel Drums
Color	Black
Dimensions	53" W x 53" L x 12" H
Recycled Content	95% Post-Industrial Recycled Polyethylene
Load Capacity UDL	5000 lbs.
Sump Capacity	66 gal.

Double-Stackable Unit	No
Drain	Optional Drain
Fork Truck Access	Four-Way Fork Access, Move Unloaded Only
Grates	(2) 48" L x 24" W Grates
Use With Flammables	No
Sold as	1 each
Weight	85 lbs.
# per Pallet	9
Composition	Sump - LDPE w/ UV Inhibitor Grate - Polyethylene
UNSPSC	24101905
Pigalog® Page Number	<u>Page 370</u>

Metric Equivalent

Dimensions	134.6cm W x 134.6cm L x 30.5cm H
Load Capacity UDL	2268 kg
Sump Capacity	249.8 L
Weight	38.6 kg

Technical Information

Technical Documents

LDPE Products

[40 CFR 112.7](#)

[40 CFR 122.26](#)

[40 CFR 264.175](#)

Disclaimers

Flammables Notice

If using this product with flammable liquids, please consider the regulations that apply to storage and handling of flammable liquids and the safety of this application, specifically flammable vapors, static discharge and heat sources. For further assistance, please call Technical Services.

Poly Drum Notice

Not recommended for long term storage of poly drums.



One Pork Avenue • Tipton, PA 16684-0304

1-855-493-4647 • Fax: 1-800-621-7447 • newpig.com • hothogs@newpig.com

