



Steel Re-Nu® Stainless Steel Coating, 13 Wt Oz
 No. 18211 | Item# 1005234 | Case# 1005233

Product Description	A coating containing 316L Stainless Steel pigment to provide corrosion resistance and protection against sunlight, oil, and water. Authorized for use in food processing plants.
Color	Gray
Applications	On threads, exposed edges, fasteners, conduit, strapping, welds, fencing, railings, grates, electrical poles, breaker panel housings, rain spouts, signs, doors, trailers, waste containers, catwalks, and guard rails.
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	316L Stainless Steel Coating
Net Fill	13 Wt Oz
UPC Code	078254182117
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	6
Case Dimensions	8.25H x 5.75W x 8.25D in
Cases Per Pallet	150
Case Weight	7 lbs
I 2 of 5 Code	30078254182118
Appearance	Gray Viscous Liquid
Flash point (F)	-2°F
Flash point (C)	-19°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.77 to 0.85
Plastic Safe	Yes
Dry Time - Fully Dry	20 Minutes
Dry Time - Tack Free	20 Minutes
Recoat	Anytime
Coverage	28 to 32 Sq Ft at 3 Mil Dry

Last revised: 7/30/2019
 Page 1 of 2





Working Temp (F)	130°F (Continuous) / 150°F (Intermittent)
Working Temp (C)	54.4°C (Continuous) / 65.6°C (Intermittent)
Propellant	Hydrocarbon
NSF Category Code	R2
NSF Number	150841
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	59.3
VOC g/L (Consumer Product def)	619
VOC lbs/gal (Consumer Prod def)	5.2
VOC Category	Aerosol Coating: Metallic
MIR Limit (EPA)	1.9
MIR Limit (CA)	1.25
MIR Value	1.24
Removal (How To)	Remove with aromatic solvents, Xylene. Toluene can be used, but is not recommended.